

Tech Specs

[UniFi](#) [UISP](#) [Branding](#)

[UniFi Cloud Gateways](#)

[WiFi](#)

[Switching](#)

[Cloud Keys & Gateways](#)

[Camera Security](#)

[Door Access](#)

[Phone System](#)

[New Integrations](#)

[Accessories](#)

[Ethernet Surge Protector](#)

[Datasheet](#)

[Marketing Images](#)

ETH-SP-G2

Dimensions	91 x 61 x 32.5 mm (3.58 x 2.4 x 1.28")
Weight	80 g
Weatherproofing	IPX5
Interface Connections	(2) RJ45 Female Connectors
ESD/EMP Protection	Absorbing Transient Current with Response to Surge Voltage from 100V/s to 1kV/ μ s
DC Spark-Over Voltage	90V @ 100V/s
Maximum Impulse Spark-Over Voltage	700V @ 1kV/ μ s
Discharge Current	10kA+
Maximum Insulation Resistance	1G ohm @ 50V
Maximum Capacitance	1.0 pF @ 1 MHz
Data Line Protection	RJ45 10/100/1000 Ethernet
PoE Support	Yes
Shock and Vibration Certification	ETSI300-019-1.4 Standard
Operating Temperature	-30 to 65° C (-22 to 149° F)
Operating Humidity	10 to 90% Noncondensing

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.